



PREMIUM GROUT & STONE SEALER

Seals Porous Stone, Tile & Grout Without Affecting Slip Resistance

It is the preferred product when applying a clear sealer to grout since it can be sprayed or sponged onto grout lines and squeegeed or mopped off non-porous ceramic and porcelain tile, decreasing the application time.

X Stone X Grout ✓ Absorbent Tile

X = Primary Use ✓ = Secondary Use



HYDRO-FORCE™

One U.S. Gallon (3.79 Litres)

Premium Grout and Stone Sealer
SHAKE THOROUGHLY BEFORE EACH USE!

DIRECTIONS FOR USE: Cleaning is necessary

Surface must be cleaned and thoroughly rinsed. The dryer the grout and stone the better the penetration. Make sure that there are no puddles in grout lines and use air movers to speed the drying of the stone and grout lines before application. If pH of surface is higher than 11, (unusual if thoroughly rinsed), then sealer may not bond properly. Stone & grout lines may need to be rinsed with neutral cleaner to lower pH of grout before application of sealer. Test for efflorescence if color of grout is not white.

Dilution Instructions

Do not dilute; ready to use. Coverage should be between 600 to 1200 sq. ft. per gallon depending on the porosity of the surfaces and the coverage required (grout only or entire surface).

Application Methods

Spray grout lines with pump up sprayer. Squeegee excess into untreated areas and bonnet off non-porous tiles. When dry (typically 1 to 2 hours) if there is a white haze on tiles, then buff off with white polishing pad and 175 rpm rotary machine. For entire floor application, spray on sealer then spread with a brush with synthetic fibers. A second coat may be necessary after 1 hour. Place drop of sealer on newly sealed grout or stone and see if it absorbs into grout or stone. If it does absorb readily, then a second coat is necessary. Test for suitability in an inconspicuous area, especially for polished marble and extremely porous surfaces.

Post Application Precautions

Floor is typically walkable in 3 to 4 hours, ready for use after 8 to 12 hours, and completely cured in 24 hours. These times will be less if only grout was sealed. After 6 to 18 months, reapplication may be necessary, depending upon the traffic

and the type of surface sealed.

CONTAINS

Isopropyl Alcohol (CAS # 67-63-0), Telomer B Phosphate (CAS # 65530-63-4), Telomer B Phosphate Diethanolamine Salt (CAS # 65530-64-5), Telomer B Phosphate Diethanolamine Salt (CAS # 65530-74-7) Water (CAS # 7732-18-5)

¡AGÍTESE BIEN ANTES DE CADA USO!

INSTRUCCIONES PARA EL USO:

Limpieza

Es necesario limpiar y enjuagar la superficie por completo. Cuanto más seca sea la lechada y la piedra, mejor será la penetración. Asegúrese de que no haya quedado ningún líquido en las líneas de lechada, y antes de aplicar el sellador, utilice aspiradores de aire para que se sequen rápidamente la piedra y la lechada. Si el valor del pH de la lechada es superior a 11 (lo que casi nunca sucede si se enjuaga bien), es probable que el sellador no se adhiera correctamente. Es posible que sea necesario enjuagar la piedra y las líneas de lechada con un limpiador neutro para reducir el valor del pH antes de aplicar el sellador. Pruebe si se cristaliza en una línea de cemento que no sea blanca.

Dilución

No diluya el sellador; úselo tal como está. Debe cubrir entre 600 y 1200 pies cuadrados (de 56 a 112 metros cuadrados) por cuarto de galón (3.785 litro), dependiendo de la porosidad de las superficies y de la cobertura requerida (superficie entera o sólo la lechada).

Métodos de aplicación

Use una bomba o un rociador para aplicar el sellador en las líneas de lechada. Utilice un escurridor de goma ("squeegee") para mover cualquier exceso del producto a las áreas no tratadas y utilice una máquina rotativa con paño tipo "bonnet" (de pelo corto) para los azulejos no porosos. Una vez que la superficie esté seca (típicamente de 1 a 2 horas), si los azulejos quedan opacos con un residuo blanco, sáqueles el brillo usando una máquina rotativa de 175 rpm con una

almohadilla blanca de pulimiento.

Para tratar todo el piso, aplíquelo con un rociador, luego espárzalo con una brocha de fibras sintéticas. Es posible que sea necesario aplicar una segunda capa después de una hora. Ponga una gota del sellador en una parte de la piedra o lechada recién sellada. Si se absorbe fácil o rápidamente, hay que aplicar una segunda capa. Haga la prueba en un área poco visible, especialmente si se trata de mármol pulido o de superficies extremadamente porosas.

IMPORTANT NOTICE TO PURCHASER: Seller's and manufacturer's liability for any and all losses or damages resulting from any cause whatsoever shall in no event exceed the purchase price of this product, with respect to which losses or damages are claimed. Before using, the user shall determine the suitability of this product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. Go to www.hydroforce.com/sds for additional safety, regulatory and liability information.

PREMIUM STONE & GROUT SEALER



May cause skin and eye irritation. Avoid contact with skin and eyes. In case of contact, immediately flush with plenty of water, seek medical advice if irritation persists.

Susceptible d'irriter la peau et les yeux. Évitez tout contact avec la peau et les yeux. S'il y a contact, lavez-vous immédiatement à la grande eau. Consultez un médecin si l'irritation se fait persistante.

SEE SAFETY DATA SHEET
VOIR LA FICHE SIGNATÉTIQUE

See Safety Data Sheet (SDS):
www.hydroforce.com/sds
for additional safety and regulatory information.

Another fine product from Hydro-Force Manufacturing
4282 South 590 West, Salt Lake City, UT 84123
www.hydroforce.com

WARNING!



Keep out of reach of children.

HAZARD STATEMENTS:
Causes eye irritation.

PRECAUTIONARY STATEMENTS:

IF IN EYES: Rinse cautiously with water for several minutes. Remove Contact Lenses, if present and easy to do. Continue rinsing.
IF ON SKIN: Wash with plenty of soap and water.
IF SKIN irritation occurs: Get medical advice/attention.

ADVERTENCIA!




Mantener fuera del alcance de los niños.

INDICACIONES DE PELIGRO:
Causa irritación al ojo.

DECLARACIONES DE PRECAUCIÓN:

Si en los ojos: Enjuagarse cuidadosamente con agua por varios minutos. Remueva lentes de contacto si los está usando. Continúe enjugándose. Si en la piel: Lavarse con amplio jabón y agua. Si irritación a la piel ocurre: Obtenga consejo/ atención médica.



CH06GL

RTU ph - 8.5